

Black

Grounding & Cleaning

If the material is used on top of an already properly grounded surface, grounding hardware may not be necessary. Where no properly grounded surface is available, grounding hardware is required to provide a path-to-ground. Rg compliance verification measurements must be made per EN 61340-5-1 periodically with a surface resistance meter.

See Tech Bulletin TB-7000 for Reztore® Surface & Mat Cleaner Application Instructions.

Limited Lifetime Warranty:

Desco Europe warrants for one year that Statfree® matting products will be free of defects in materials and workmanship and will guarantee dissipative/conductive mat properties for the life of the mat. Damage to matting caused by misuse of any kind, including using inappropriate cleaners is not covered by Desco Europe Limited Warranty.

RoHS 3, REACH, and Conflict Minerals Statement
See the Desco Europe RoHS 3, REACH, and Conflict Minerals
Statement

DescoEurope.com/ROHS.aspx

See the Desco Europe Limited Warranty: DescoEurope.com/Limited-Warranty.aspx

See the Desco Europe Disclaimer: DescoEurope.com/Disclaimer.aspx



Standard Document Meets Requirements of:

EN 61340-5-1 Flooring

Electrical Properties

Property Test Method Value

Rp-p Resistance: IEC 61340-4-1 $1 \times 10^4 \text{ to} < 1 \times 10^6 \text{ ohms}$ Rg Resistance: IEC 61340-4-1 $1 \times 10^4 \text{ to} < 1 \times 10^6 \text{ ohms}$

Electrical Properties obtained by testing to industrial standards by an independent testing laboratory at 10 Volts and 50% relative humidity unless otherwise specified. Complete text of the test report is available upon request.

Physical Properties

Thickness: 12.7mm
Color:* Black
Texture:* Bubble cells

Tolerances

Width ± 6.35mm

Length ± 6.35mm every 0.305m of running material

*Colour, texture, and gauge may vary between lots and mills



Specifications and procedures subject to change without notice.

Statfree i™ Interlocking Room System, Conductive, Ergonomic, 12.7mm





Drawing Number PME-i

DATE: September 2017